

# THE ENGWALD CORPORATION

## NEOPRENE COATED HOSES

### SERIES RFH (EPDM COATED) RUBBER HOSE

**Series RFH** hose is a high strength, lightweight thermoplastic rubber coated hose with a .060" diameter spring steel wire helix for structure and support. It is well suited for use on the hose reels where high temperatures are not a factor. It comes available in 3", 4", 5" and 6" diameters and in lengths of 18' or 24'. Maximum negative pressure is 6" W.G. Its temperature range is from -40 degrees F to +275 degrees F with intermittent maximum of 325 degrees F.



***Large Diameter and Customized Lengths Available***

- Moisture Resistance
- UV Resistance
- Outstanding Flex Fatigue Resistance
- Good Tear Resistance
- Improved Puncture Resistance
- Better Chemical Resistance
- Higher Temperature Resistance
- Better Weathering Characteristics
- Will Not Flake Off Its Coating After Repeated Flexing
- No Cements, Glues or Adhesives

Job Name: \_\_\_\_\_ No. of Hoses: \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_ Length of Hose: \_\_\_\_\_

Contractor: \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_ Diameter: \_\_\_\_\_

Remarks: \_\_\_\_\_ Tailpipe Adapter: \_\_\_\_\_

\_\_\_\_\_  
 \_\_\_\_\_  
 \_\_\_\_\_

